



\* Anti-Spark Hose

Product Data - Medium Reels Air

Art.no.	Hose length	Dim. (IDxOD)	Conn. 1	Conn. 2	WP bar (psi)	Weight (kg)
19 911 2120	17	8x12	R 1/4"	R 1/4"	16 (232)	6,0
19 911 2121	17	8x12	1/4" NPT	1/4" NPT	16 (232)	6,0
19 911 2130	14	9,5x13,5	R 3/8"	R 3/8"	16 (232)	5,9
19 911 2131	14	9,5x13,5	3/8" NPT	3/8" NPT	16 (232)	5,9
19 911 2132	14	9,5x13,5*	R 3/8"	R 3/8"	12 (174)	5,9
19 911 2133	14	9,5x13,5*	3/8" NPT	3/8" NPT	12 (174)	5,9
19 911 2140	10	11x16	R 1/2"	R 1/2"	12 (174)	6,3
19 911 2141	10	11x16	1/2" NPT	1/2" NPT	12 (174)	6,3
19 911 2150	8	13x18	R 1/2"	R 1/2"	10 (145)	6,3
19 911 2151	8	13x18	1/2" NPT	1/2" NPT	10 (145)	6,3
19 911 2180	17	8x12	300-nipple	300 eSafe	16 (232)	6,0
19 911 2181	17	8x12	310-nipple	310 eSafe	16 (232)	6,0
19 911 2182	17	8x12	320-nipple	320 eSafe	16 (232)	6,0
19 911 2183	17	8x12	315-nipple	315 eSafe	16 (232)	6,0

Technical Data:

Feeder hose length: 1,5m  
 Hose material: Braided PUR (ester based)  
 Connections: Male thread  
 Temperature range: -20°C - +60°C (-4°F - +140°F)  
 Sealing material: NBR



Scale	1 : 4	Drawn	CABJOOL	Checked	CABFA	Appr.	CABOG	ECO	11771	Date	2017-07-06	
Drawing No.							509119901		Issue	X1	Sheet	1 / (1)

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©

A3