

4 **L7556... (VS400)** | 6/2 ways/positions piloted flow diverters - Size 16
 Technical data

Electrical							
Voltage type		DC					
Voltage tolerance (nominal voltage)	%	-10 +10					
Duty		Continuous (100%), with ambient temperature ≤ 50°C (122°F)					
Coil wire temperature not to be exceeded	°C (°F)	150 (302)					
Insulation class		H					
Compliance with		Low Voltage Directive LVD 73/23/EC (2006/95/EC), 2004/108/EC					
Coil weight with connection EN 175301-803	kg (lbs)	0.215 (0.44)					
Voltage	V	12	13	24	27	48	110
Voltage type		DC	DC	DC	DC	DC	DC
Power consumption	W	26	26	26	26	26	26
Current (nominal at 20 °C (68 °F))	A	2.15	2.00	1.10	1.00	0.54	0.27
Resistance (nominal at 20 °C (68 °F))	Ω	5.5	6.5	22	28	89	413

Note

For applications with different specifications consult us

Code	Voltage (V)	Connector type	Coil description	Marking	Coil Mat no.
OB 01	12 DC	EN 175301-803 (Ex. DIN 43650)	C3601 12DC	12 DC	R933000044
OB 03	12 DC	AMP JUNIOR	C3603 12DC	12 DC	R933000047
OB 04	12 DC	AMP JUNIOR Horizontal	C3604 12DC	12 DC	R933002913
OB 07	12 DC	DEUTSCH DT 04-2P	C3607 12DC	12 DC	R933000048
OB 31	12 DC	Cable 350 mm long	C3631 12DC	12 DC	R933000045
AD 01	13 DC	EN 175301-803 (Ex. DIN 43650)	C3601 13DC	13 DC	R933000051
AD 07	13 DC	DEUTSCH DT 04-2P	C3607 13DC	13 DC	R933000049
OC 01	24 DC	EN 175301-803 (Ex. DIN 43650)	C3601 24DC	24 DC	R933000053
OC 03	24 DC	AMP JUNIOR	C3603 24DC	24 DC	R933000057
OC 04	24 DC	AMP JUNIOR Horizontal	C3604 24DC	24 DC	R933002914
OC 07	24 DC	DEUTSCH DT 04-2P	C3607 24DC	24 DC	R933000058
OC 31	24 DC	Cable 350 mm long	C3637 24DC	24 DC	R933000055
AC 01	27 DC	EN 175301-803 (Ex. DIN 43650)	C3601 27DC	27 DC	R933000056
AC 07	27 DC	DEUTSCH DT 04-2P	C3607 27DC	27 DC	R933000050
OD 01	48 DC	EN 175301-803 (Ex. DIN 43650)	C3601 48DC	48 DC	R933000059
OD 04	48 DC	AMP JUNIOR Horizontal	C3604 48DC	48 DC	R933002915
OE 01	110 DC	EN 175301-803 (Ex. DIN 43650)	C3601 110DC	110 DC	R933000061

Electric connection

