

Counterbalance, vented guided poppet type, counterclockwise adjustment  
Sun cavity interchange, T-17A


VBST-16U-RS

04.59.31 - X - 47 - Z

**RE 18320-25**

Edition: 07.2023

Replaces: 01.2021




**Technical data**

Max. operating pressure	350 bar (5000 psi)
Max. flow	240 l/min (63 gpm)
Max. internal leakage <sup>1)</sup>	15 drops/min.
Fluid temperature range	-30 to 100 °C (-22 to 212 °F)
Installation torque	200 - 215 Nm (148 - 159 ft-lbs)
Weight	0.8 kg (1.76 lbs)
MTTFD	150 years see RE 18350-51
Cavity	SUN T-17A
Adjustment	according to ISO 4413 with sealed adjustment screw to prevent oil leakage during adjustment
Salt spray test	500h according to DIN EN ISO 9227:2017-07
Lines bodies and standard assemblies	Please refer to section "Hydraulic integrated circuit" or consult factory
Seal kit <sup>2)</sup>	Code: RG16U9020110100 material no: R930000995
Fluids	Mineral-based or synthetics with lubricating properties at viscosities of 10 to 500 mm <sup>2</sup> /s (cSt)
Recommended degree of fluid contamination	Nominal value max. 10µm (NAS 8) / ISO 4406 19/17/14
Installation position	No restrictions
Other Technical Data	See data sheet 18350-50

Pressure setting: at least 1.3 times the load induced pressure and maximum 1.5 times catalogue max nominal setting.


- 1) At 70% of pressure setting
- 2) Only external seals for 10 valves

**Characteristic curve**



**Description**

When pressure at 2 rises above the spring bias pressure, the check seat is pushed away from the piston and flow is allowed from 2 to 1. When load pressure at 1 rises above the pressure setting (turn counterclockwise to increase setting - turn clockwise to decrease setting), the direct-acting, relief function is activated and flow is relieved from 1 to 2. With pilot pressure at 3, the pressure setting is reduced in proportion to the stated ratio of the valve, until fully open with free-flow from 1 to 2. The spring chamber is vented to atmosphere allowing operation of all functions independent of back-pressure at 2. Valve design prevents spring going solid and complete unscrewing during adjusting.



**Ordering code**

<b>04.59.31</b>	<b>X</b>	<b>47</b>	<b>Z</b>	<b>*</b>	<b>*</b>
-----------------	----------	-----------	----------	----------	----------

Counterbalance, vented guided poppet type, counterclockwise adjustment

Pilot ratio

**03** 3:1

**47** SUN cavity interchange, T-17A

Series M to Z unchanged performances and dimensions

**00** Standard (Buna)  
**V0** Viton (FKM)

	SPRINGS		
	Adj. press. range bar (psi)	Pressure increase bar/turn (psi/turn)	Std. setting bar (psi) cracking pressure
<b>20</b>	70-250 (1000-3600)	70 (1015)	200 (2900)
<b>40</b>	200-350 (2900-5000)	105 (1523)	350 (5000)


Note: Special settings available with optional tamperproof cap. Contact factory authorized representative for ordering code.

**Preferred types**

Type	Material number
04593103472000M	R930081340
04593103474000M	R930081341

Type	Material number
045931034720V0M	R930081379

**Dimensions**



Turn adjustment clockwise to decrease setting and release load

**OPTION**  
Protection cap orange  
Mat. no. R900168151  
  
Tamper proof cap black  
Mat. no. R930092782

**Bosch Rexroth Oil Control S.p.A.**

Via Leonardo da Vinci 5  
P.O. Box no. 5  
41015 Nonantola – Modena, Italy  
Tel. +39 059 887 611  
Fax +39 059 547 848  
compact-hydraulics-cv@boschrexroth.com  
www.boschrexroth.com/compacthydraulics

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth Oil Control S.p.a.. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging. Subject to change.